

BAGMATIC 6 stations / 5 colors		DESCRIPTION	LIST PRICE				
		DESCRIPTION	LISTTRICE				
Machine							
1	Total diameter	240 cm					
2	Base diameter	105 cm					
3	Total weight	1100 kg					
4	High	134 cm					
5	Air consumption / pressure	304 l/min, 6 bar(90psi)					
6	Electrical requirements	400V, 3PH, 5.5 kW, 32A CEE-plug					
7	Max PRINT area	30 x 30 cm (12" x 12")					
8	Direction	CCW, CW					
9	Max print speed	1100 cycle/hour					
10	Squeegee & Flood speed	Independent for each printing head					
11	Guarantee	2 years limited warranty					
12	Multi print	Multiple print for chosen print head					
13	MULTIPRINT table UP/DOWN	Choice of table position in MULTIPRINT mode					
14	MULTIPRINT FLASHING function	Possibility to PRINT -FLASH -GO BACK-PRINT AGAIN					
15	Test print	Possibility to run press in test print mode for individual print head or for all colors					
16	Free wheel	Possibility to unlock indexer to move lower wheel with table by hand					
17	Max Screen Size	46 x 60 cm					
18	Programing machine cycle	Possibility to program for special sequence printing system					
19	Water base print system	The software is prepared to choose between plastisol or water base ink					
20	Half Index	Possibility to move lower wheel in half rotation of full index. CW and CCW direction available					
21	Wide range of machine's speed adjustment	Possibility to change velocity and acceleration of machine, 2 programmable delays in machine's cycle					
22	PALLET MODE function	Possibility to change velocity and acceleration of machine, 2 programmable delays in machine's cycle					
23	DOUBLE INDEX function	Possibility to produce 2 orders together, even colors print first job, odd colors print second job					

	MACHINE	EQUIPMENT IN S	TANDAI	R D	
24	Servo INDEX	Very precision rotation system, smooth operation, velocity and acceleration change possibility	1		INCLUDED
25	Electric Print Heads	Gives smooth SQ&FL operation, in all range of speed	5		INCLUDED
26	Pneumatic lift	Pneumatic cylinder 4"	1		INCLUDED
27	Central OFF Contact	Manual off-contact change	1		INCLUDED
28	Measure indicator for print stroke	Easy to read and change print stroke length and position	5		INCLUDED
29	Screen AIR locking / per head	Four pneumatic cylinder per screen	5		INCLUDED
30	Skip Switch	On the control panel, in automatic mode foot pedal works as skip button	1		INCLUDED
31	Quick change Slide Mount pallets system	Easy & fast to change pallets	6		INCLUDED
32	Pneumatic fasten Squeegee & Flood	Pneumatic SQ & FL fasten	Option		See below
33	All function control access from head key board	Gives access to all head operation and some main operations	5		INCLUDED
34	Foot Pedal	In manual mode works as START button, in AUTO mode works as SKIP button	Option		See below
35	Main air regulator with water filter, oil lubrication & low air pressure switch	Easy to control and service air pressure with oil tank to keep all pneumatic parts in good condition	1		INCLUDED
36	Side (left & right) screen holders	Better screen positioning, easy flash operations	5		INCLUDED
37	Micro Adjustment	Very precision screen's micro registration	5		INCLUDED
38	Micro Dial Indicator	Simple indicator to screen movements	5		INCLUDED
39	load and unload safety System	Electric safety bars protecting load and unload positions while machine rotate	1		INCLUDED
40	Squeegee & Flood mechanical pressure regulation	SQ&FL piston stroke adjustment, in combination with angle adjustments gives control over rubber-screen tension force	1		INCLUDED
41	Squeegee air Pressure Regulation	Access to gouge on every print head lets you to control the SQ air pressure	5		INCLUDED
42	Print head reduction	- € 600 for take off print head; additional head in the future cost 3200€	Choice		See below
43	1set FREE Squeegee/Flood	12" length	1		INCLUDED
44	1set FREE Pallets	aluminum rubber coated; size 12" x 16 "	1		INCLUDED

	МАСНІМЕ	E Q U I P M E N T I N	O P T I O N	1	
45	Pneumatic fasten Squeegee & Flood	+ €200 per print head	0		
46	1 set extra aluminum pallets cm	Aluminum rubber coated; size cm	0		
47	1 set extra squeegee with blade 70 durometer	The length cm	0		
48	1 set extra aluminum flood bar	The length cm	0		
49	Foot Pedal	Let you to control the press by foot switch	1		INCLUDED
50	Printing head reduction on the press	Reduction printing heads in relation to standard size	0		
51	Pallet Locator	Easy and convenient pallet placing	0		
52	IR Carbon Quartz Flash CLH 1212	Quartz Infrared heater, heat area 12 x 12", Electronic power control, pallet temperature sensor, temperature setting and reading max power 6 kW (auto or manual control)	0		