

**GAS DRYING TUNNEL GAL-72146**

**MACHINE**

|           |                         |                                                         |                         |                         |
|-----------|-------------------------|---------------------------------------------------------|-------------------------|-------------------------|
| <b>1</b>  | Total length            | 614 cm                                                  |                         |                         |
| <b>2</b>  | Heat chamber length     | 370 cm                                                  |                         |                         |
| <b>3</b>  | Belt width              | 182 cm                                                  |                         |                         |
| <b>4</b>  | Inlet / outlet length   | 120 cm                                                  |                         |                         |
| <b>6</b>  | High                    | 130 cm                                                  |                         |                         |
| <b>7</b>  | Electrical requirements | 400V, 3PH, 3 kW, 32A CEE-plug                           |                         |                         |
| <b>8</b>  | Belt rotation direction | Both side( left & right )                               |                         |                         |
| <b>9</b>  | Belt drive              | frequency converter, sleeplessly adjustable 1 – 5 m/min |                         |                         |
| <b>10</b> | Belt type               | fiberglass Teflon coated, 4x4 mm mesh-size              |                         |                         |
| <b>11</b> | Exhaust connection      | 150 cm                                                  |                         |                         |
| <b>12</b> | Heating elements        | GAS BURNER, HEAT EXCHANGER, HOT AIR FREE OF FUMES       |                         |                         |
| <b>13</b> | GAS BURNER TYPE         | <b>min power 20 kW</b>                                  | <b>max power 70 kW</b>  |                         |
| <b>14</b> | GAS Consumption         | <b>AVERAGE at 180°C<br/>4,2 litres/h</b>                | <b>Min 2,1 litres/h</b> | <b>Max 7,3 litres/h</b> |
| <b>15</b> | Hot air circulation     | INCLUDED                                                |                         |                         |
| <b>16</b> | Temperature control     | PID                                                     |                         |                         |
| <b>17</b> | Light tower             | Signalize STAGES OF MACHINE                             |                         |                         |
| <b>18</b> | Warranty                | 2 years limited warranty                                |                         |                         |